Product datasheet

Specification





Backplane, Modicon X80, 8 slots, panel, mounitng plate or DIN rail mounting

BMXXBP0800

Main

Range Of Product	Modicon X80
Product Or Component Type	Backplane

Complementary

,		
Number Of Slots	8 bus X	
Product Compatibility	BMXP34 processor BMXCPS power supply	
	I/O module	
	Specific application module	
Power Consumption In W	2.21 W	
Electrical Connection	1 connector (XBE) expansion module	
Fixing Mode	By 4 M4/M5/M6 screws, mounting on panel By 4 M4/M5/M6 screws, mounting on mounting plate By clips, mounting on 35 mm symmetrical DIN rail	
Height	103.7 mm	
Width	372.8 mm	
Depth	19 mm	
Net Weight	0.95 kg	

Environment

Ip Degree Of Protection	IP20		
Ambient Air Temperature For Operation	060 °C		
Relative Humidity	1095 % without condensation		
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility		
Product Certifications	CE UL CSA RCM EAC UKCA Merchant Navy		
Standards	EN/IEC 61131-2 EN/IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201		

EN/IEC 61000-6-5, interface type 1 and type 2

EN/IEC 61850-3, location G

IACS E10

Packing Units

18 May 2024 Life Is On Schneider 1



Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.600 cm
Package 1 Width	15.300 cm
Package 1 Length	45.500 cm
Package 1 Weight	996.000 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	9
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	9.783 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	54
Package 3 Height	104.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	66.280 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Circularity Profile	End of Life Information	

Product datasheet

BMXXBP0800

Dimensions Drawings

Dimensions




BMXXBP0800

Mounting and Clearance

Minimum Clearance

Minimum Clearance of a typical installation in a cabinet with ducts




- a Side clearance: > 40 mm (1.57 in.)
- **b** Top and bottom clearance with surrounding objects: > 20 mm (0.79 in.)
- 1 Installation or casing
- 2 Wiring duct or tray

Mounting on DIN rail

Symmetric DIN rail		5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5	
Туре А	Туре В	Double-profile DIN rail	
35.0 	mm 61.0 88:1 7.2 0.28	7.2 0.28 98.1 0.59	

NOTE: When mounted on a type B symmetric DIN rail, the rack withstands less mechanical stress.


Mounting on panels



Rack Type	а	b	
X Bus racks	BMXXBP0400 BMXXBP0400H	202.1 mm (7.957 in)	214.8 mm (8.457 in)
	BMXXBP0600 BMXXBP0600H	267.5 mm (10.531 in)	280 mm (11.023 in)
	BMXXBP0800 BMXXBP0800H	332.5 mm (13.091 in)	345.2 mm (13.591 in)
	BMXXBP1200 BMXXBP1200H	462.9 mm (18.224 in)	475.6 mm (18.724 in)

18 May 2024

Mounting on Telequick mounting plate



1 Telequick plate 2 Clip-on nuts

NOTE: The two right side screws are accessible until there is no rack extender module installed